



## The Most Popular Electronic Flash Unit for 35mm SLR Photography

### FEATURES

- Guide number 120 (ISO 100/feet) 37 (DIN 21/m). Powerful automatic exposure range from 3 to 43 ft.
- Four auto f stop settings for controlling depth-of-field and maximum auto flash range.
- Vertical bounce flash for softer, professional quality lighting.
- Removable flash sensor can be camera mounted with the optional SC-1 sensor cord.
- Optional VP-1 variable power control for convenient fill flash and rapid sequence photography.
- Auto Thyristor™ circuitry for faster recycle time and greater number of flashes.
- Lighted, easy-to-use calculator dial and sufficient light indicator.

### SPECIFICATIONS

<b>Guide Number</b>	120 (ISO 100/feet) 37 (DIN 21/m)
<b>Auto Flash Range</b>	3-43 ft. (1-13.1m)
<b>Auto f/ Stop Range</b>	f/2.8 5-43 ft. (1.5-3m) f/4 4-30 ft. (1.2-9m) f/8 3-15 ft. (0.9-4.5m) f/11 3-11 ft. (0.9-3.4m)
<b>Auto Thyristor™ Circuitry</b>	Yes
<b>Vertical Bounce Flash</b>	Four positions - 45°, 60°, 75°, 90°
<b>Variable Power Control</b>	Yes, with optional VP-1 adapter (#238278)
<b>Remote Sensor Capability</b>	Yes, with optional SC-1 sensor cord (#235026)
<b>Sufficient Light Indicator</b>	Yes
<b>Flash Test Button</b>	Yes
<b>Flash Ready Indicator</b>	Yes
<b>Film Speed Range</b>	ISO 64-1000
<b>Power Source</b>	Uses 4 AA alkaline batteries
<b>NiCad Capability</b>	Yes - with NC-3 battery (#239460)
<b>Dimensions</b>	4.9x3.7x3.7 inches (125x95x95mm)
<b>Weight</b>	13.5ounces (373 grams)
<b>Accessories Included</b>	PC cord
<b>Stock Number</b>	233952